

09.2025

11,69	+ -	0,67
-------	-----	------



Spring test acc. to DIN ISO 2859/1 test level II

1 Coiling direction left right	4 Stress cyc. end. <u>N</u>																										
2 Loop shape and loop position Loop shape 1/1 German loop Loops offset to one another by 180,0 + 48,0 degrees (in the dir. of the right helix)	5 Stress cycle frequ. <u>n</u> / 6 Application temp. °C 7 Material EN 10270-1 8 Wire or rod surface ☒ drawn ☐ rolled ☐ metal-cut 9 Surface treatment																										
3 Excursion <u>sh</u> mm Remarks Zem pvodu: DE íslo celního sazebníku: 73202085																											
10 Tolerances to DIN 2097 <table><tr><th>Grade</th><th>De,Di,D</th><th>L0</th><th>F0-Fn</th><th>Loops</th><th>Wire diameter d to DIN 2076</th></tr><tr><td>1</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td></td></tr><tr><td>2</td><td>☒</td><td>☒</td><td>☒</td><td>☒</td><td></td></tr><tr><td>3</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☒</td></tr></table>		Grade	De,Di,D	L0	F0-Fn	Loops	Wire diameter d to DIN 2076	1	☐	☐	☐	☐		2	☒	☒	☒	☒		3	☐	☐	☐	☐	☒		
Grade	De,Di,D	L0	F0-Fn	Loops	Wire diameter d to DIN 2076																						
1	☐	☐	☐	☐																							
2	☒	☒	☒	☒																							
3	☐	☐	☐	☐	☒																						
11 Production compensation through <table><tr><td>A spring resistance, associated length of tensed spring and L0</td><td>F0, D</td><td>☒</td></tr><tr><td>A spring resistance, associated length of tensed spring and F0</td><td>L0, n, d</td><td>☐</td></tr><tr><td></td><td>L0, D</td><td>☐</td></tr><tr><td>Two spring resistances and associated length of tensed spring</td><td>L0, n, d</td><td>☐</td></tr><tr><td></td><td>F0,D</td><td>☐</td></tr></table>		A spring resistance, associated length of tensed spring and L0	F0, D	☒	A spring resistance, associated length of tensed spring and F0	L0, n, d	☐		L0, D	☐	Two spring resistances and associated length of tensed spring	L0, n, d	☐		F0,D	☐											
A spring resistance, associated length of tensed spring and L0	F0, D	☒																									
A spring resistance, associated length of tensed spring and F0	L0, n, d	☐																									
	L0, D	☐																									
Two spring resistances and associated length of tensed spring	L0, n, d	☐																									
	F0,D	☐																									
Prices <table><tr><th>Stupnice množství</th><th>Jedn. cena [EUR]</th></tr><tr><td>1</td><td>6,0900 €</td></tr><tr><td>2</td><td>3,8400 €</td></tr><tr><td>3</td><td>2,2300 €</td></tr><tr><td>7</td><td>1,8600 €</td></tr><tr><td>17</td><td>0,9400 €</td></tr><tr><td>37</td><td>0,5800 €</td></tr><tr><td>75</td><td>0,4000 €</td></tr><tr><td>125</td><td>0,3775 €</td></tr><tr><td>175</td><td>0,3713 €</td></tr><tr><td>250</td><td>0,3676 €</td></tr><tr><td>350</td><td>0,3582 €</td></tr><tr><td>450</td><td>0,3516 €</td></tr></table>		Stupnice množství	Jedn. cena [EUR]	1	6,0900 €	2	3,8400 €	3	2,2300 €	7	1,8600 €	17	0,9400 €	37	0,5800 €	75	0,4000 €	125	0,3775 €	175	0,3713 €	250	0,3676 €	350	0,3582 €	450	0,3516 €
Stupnice množství	Jedn. cena [EUR]																										
1	6,0900 €																										
2	3,8400 €																										
3	2,2300 €																										
7	1,8600 €																										
17	0,9400 €																										
37	0,5800 €																										
75	0,4000 €																										
125	0,3775 €																										
175	0,3713 €																										
250	0,3676 €																										
350	0,3582 €																										
450	0,3516 €																										