


d mm Wire diameter
D mm Mean coil diameter
Dd mm Diameter of mandrel
De mm Outer coil diameter
Dh mm Diameter of bush
e1 mm Perm.dev. perpendicular line
e2 mm Perm.dev. parallel line
F1 N Prestressed spring force
F2 N Loaded spring force

F_n N Maximum force in static use
F_c N Theoretic maximum force at L_c
L0 mm Length of unstressed spring
L1 mm Prestressed spring length
L2 mm Loaded spring length
L_k mm Buckling length
L_n mm Minimum length in static use
L_c mm Block length
n pc. Active coils

nt pc. Total coils
R N/mm Spring rate
S mm Pitch (distance between coils)
s1 mm Prestressed spring deflection
s2 mm Loaded spring deflection
sh mm Maximum stroke in static use
sn mm Maximum spring deflection in static use
Weight g Weight of one spring in grammes

F_{ndyn} N Maximum force in dynamic force
F_{ndtol} N (+/-) tolerance of maximum dynamic force
L_{ndyn} mm Minimum length in dynamic use
sh_{dyn} mm Maximum stroke in dynamic use

* The spring data for the dynamic applications is relevant only for springs having a shot peened hardened surface !



Spring test acc. to DIN ISO 2859/1 test level II

1 Coiling direction

☐ left ☒ right

2 Dynamic load *

F_{ndyn} 4,30
F_{ndtol} 0,44
L_{ndyn} 13,05
sh_{dyn} 8,27

3 Excursion sh

mm

4 Stress cyc. end. N

5 Stress cycle frequ. n

/

6 Application temp.

°C

7 Guidance and seat to DIN EN 13906-1

☐ mandrel ☐ bush

8 Material

EN 10270-1

9 Wire or rod surface

☒ drawn ☐ rolled ☐ metal-cut

10 Springs deburred

☐ inside ☐ outside

11 Surface treatment

☐ shot peened

12 Tolerances to DIN EN 15800

Grade De, Di, D L0 F1, F2 e1, e2 Wire diameter d to DIN 2076

1 ☐ ☐ ☐ ☐ ☐ ☐ ☐

2 ☒ ☒ ☒ ☒ ☒ ☒ ☒

3 ☐ ☐ ☐ ☐ ☐ ☐ ☒

13 Production compensation through

A spring resistance and associated length of tensed spring L0 ☐

A spring resistance, associated length of tensed spring and L0 n, d ☒

Two spring resistances and associated lengths of tensed spring L0, n, d ☐

L0, n, De, Di ☐

14 Setting springs

All springs which show setting tendency because of their size are pre-set within the production process.

Prices

Stupnice množství Jedn. cena [EUR]

1 4,7200 €

2 3,3300 €

3 3,1700 €

7 1,7700 €

17 0,7400 €

37 0,4200 €

75 0,2000 €

125 0,1664 €

175 0,1253 €

250 0,1002 €

350 0,0758 €

450 0,0694 €