


α	degree	Unstressed leg position
α_1	degree	Prestressed rotational angle
α_2	degree	Loaded rotational angle
αh	degree	Excursion
αn	degree	Maximum rotational angle
d	mm	Wire diameter
Ddmin	mm	Min. possible mandrel diameter
Ddmax	mm	Max. possible mandrel diameter
De	mm	Outer coil diameter
Di	mm	Inner coil diameter
F1	N	Prestressed spring force
F2	N	Loaded spring force
Lk0	mm	Length of spring body when relaxed
LS	mm	Length of leg
M1	Nmm	Prestressed torque
M2	Nmm	Loaded torque
Mn	Nmm	Maximum torque
n	pc.	Active coils
RH	mm	Distance power flow point from centre
St	mm	Distance between coils (pitch)
Weight	g	Weight of one spring in grammes



Spring test acc. to DIN ISO 2859/1 test level II

1 Coiling direction ☒  left ☐  right	5 Excursion <u>α</u> deg.	12 Tolerances to DIN 2194 <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Grade</th> <th>Di</th> <th>Lk0</th> <th>LSH,LSR</th> <th>$\alpha, \alpha 1, \alpha 2$</th> <th>M1,M2</th> <th>Wire diameter d to DIN 2076</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☐</td> <td rowspan="3" style="text-align: center; vertical-align: middle;">d to DIN 2076</td> </tr> <tr> <td>2</td> <td>☒</td> <td>☒</td> <td>☒</td> <td>☒</td> <td>☒</td> </tr> <tr> <td>3</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☒</td> </tr> </tbody> </table>	Grade	Di	Lk0	LSH,LSR	$\alpha, \alpha 1, \alpha 2$	M1,M2	Wire diameter d to DIN 2076	1	☐	☐	☐	☐	☐	d to DIN 2076	2	☒	☒	☒	☒	☒	3	☐	☐	☐	☐	☒
Grade	Di		Lk0	LSH,LSR	$\alpha, \alpha 1, \alpha 2$	M1,M2	Wire diameter d to DIN 2076																					
1	☐		☐	☐	☐	☐	d to DIN 2076																					
2	☒	☒	☒	☒	☒																							
3	☐	☐	☐	☐	☒																							
2 Form of legs tangential, straight, no bends *  *We can also supply torsion springs with any form of leg for an extra charge.	6 Stress cyc. end. <u>N</u>																											
3 Fixing Recumbent leg Lever leg 	7 Stress cycle frequ. <u>n</u> /																											
4 Load ☐ in winding direction ☐ against winding direction	8 Application temp. °C																											
9 Material 1.4310		13 Production compensation through <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%;">A spring torque and the associated swing angle</td> <td style="width: 20%; text-align: center;">α ☒</td> </tr> <tr> <td>A spring torque and the associated swing angle and $\alpha 0$</td> <td>n, d ☐</td> </tr> <tr> <td></td> <td>n, Di ☐</td> </tr> <tr> <td>Two spring resistances and the associated swing angle</td> <td>α, n, d ☐</td> </tr> <tr> <td></td> <td>α, n, Di ☐</td> </tr> </table>	A spring torque and the associated swing angle	α ☒	A spring torque and the associated swing angle and $\alpha 0$	n, d ☐		n, Di ☐	Two spring resistances and the associated swing angle	α , n, d ☐		α , n, Di ☐																
A spring torque and the associated swing angle	α ☒																											
A spring torque and the associated swing angle and $\alpha 0$	n, d ☐																											
	n, Di ☐																											
Two spring resistances and the associated swing angle	α , n, d ☐																											
	α , n, Di ☐																											
10 Wire or rod surface ☒ drawn ☐ rolled ☐ metal-cut																												
11 Surface treatment 																												
Prices <table style="width: 100%;"> <tr> <td style="width: 40%; text-align: right;">Stupnice množství</td> <td style="width: 60%; text-align: left;">Jedn. cena [EUR]</td> </tr> <tr> <td style="text-align: right;">1</td> <td>5,5300 €</td> </tr> <tr> <td style="text-align: right;">2</td> <td>3,9000 €</td> </tr> <tr> <td style="text-align: right;">3</td> <td>2,7100 €</td> </tr> </table>			Stupnice množství	Jedn. cena [EUR]	1	5,5300 €	2	3,9000 €	3	2,7100 €																		
Stupnice množství	Jedn. cena [EUR]																											
1	5,5300 €																											
2	3,9000 €																											
3	2,7100 €																											

Remarks

Zem pôvodu: DE | číslo celného sazebníku: 73202089

13	Production compensation	through
A spring torque and the associated swing angle	α	☒
A spring torque and the associated swing angle and α_0	n, d	☐
	n, Di	☐
Two spring resistances and the associated swing angle	α, n, d	☐
	α, n, Di	☐

Prices

Stupnice množství	Jedn. cena [EUR]
1	5,5300 €
2	3,9000 €
3	3,7100 €
7	2,9000 €
17	1,4300 €
37	1,1000 €
75	0,9400 €
125	0,6511 €
175	0,6135 €
250	0,5760 €
350	0,5306 €
450	0,4927 €