



06.2025



α	degree	Unstressed leg position
α_1	degree	Prestressed rotational angle
α_2	degree	Loaded rotational angle
αh	degree	Excursion
αn	degree	Maximum rotational angle
d	mm	Wire diameter
Ddmin	mm	Min. possible mandrel diameter
Ddmax	mm	Max. possible mandrel diameter
De	mm	Outer coil diameter
Di	mm	Inner coil diameter
F1	N	Prestressed spring force
F2	N	Loaded spring force
Lk0	mm	Length of spring body when relaxed
LS	mm	Length of leg
M1	Nmm	Prestressed torque
M2	Nmm	Loaded torque
Mn	Nmm	Maximum torque
n	pc.	Active coils
RH	mm	Distance power flow point from centre
St	mm	Distance between coils (pitch)
Weight	g	Weight of one spring in grammes



Spring test acc. to DIN ISO 2859/1 test level II

1 Coiling direction ☐ left ☒ right	5 Excursion <u>a_h</u> degr.	12 Tolerances to DIN 2194 <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>Grade</th> <th>Di</th> <th>Lk0</th> <th>LSH,LSR</th> <th>$\alpha, \alpha 1, \alpha 2$</th> <th>M1,M2</th> <th>Wire diameter d to DIN 2076</th> </tr> <tr> <td>1</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☐</td> <td></td> </tr> <tr> <td>2</td> <td>☒</td> <td>☒</td> <td>☒</td> <td>☒</td> <td>☒</td> <td></td> </tr> <tr> <td>3</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☐</td> <td>☒</td> </tr> </table>	Grade	Di	Lk0	LSH,LSR	$\alpha, \alpha 1, \alpha 2$	M1,M2	Wire diameter d to DIN 2076	1	☐	☐	☐	☐	☐		2	☒	☒	☒	☒	☒		3	☐	☐	☐	☐	☐	☒
Grade	Di		Lk0	LSH,LSR	$\alpha, \alpha 1, \alpha 2$	M1,M2	Wire diameter d to DIN 2076																							
1	☐		☐	☐	☐	☐																								
2	☒	☒	☒	☒	☒																									
3	☐	☐	☐	☐	☐	☒																								
2 Form of legs tangential, straight, no bends * *We can also supply torsion springs with any form of leg for an extra charge.	6 Stress cyc. end. N																													
3 Fixing Recumbent leg Lever leg 	7 Stress cycle frequ. n /																													
4 Load ☐ in winding direction ☐ against winding direction	8 Application temp. °C																													
9 Material 		13 Production compensation through <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="padding: 5px;">A spring torque and the associated swing angle</td> <td style="width: 50px; text-align: center;">α</td> <td style="width: 50px; text-align: center;">☒</td> </tr> <tr> <td style="padding: 5px;">A spring torque and the associated swing angle and $\alpha 0$</td> <td style="text-align: center;">n, d</td> <td style="text-align: center;">☐</td> </tr> <tr> <td style="padding: 5px;"></td> <td style="text-align: center;">n, Di</td> <td style="text-align: center;">☐</td> </tr> <tr> <td style="padding: 5px;">Two spring resistances and the associated swing angle</td> <td style="text-align: center;">α, n, d</td> <td style="text-align: center;">☐</td> </tr> <tr> <td style="padding: 5px;"></td> <td style="text-align: center;">α, n, Di</td> <td style="text-align: center;">☐</td> </tr> </table>	A spring torque and the associated swing angle	α	☒	A spring torque and the associated swing angle and $\alpha 0$	n, d	☐		n, Di	☐	Two spring resistances and the associated swing angle	α , n, d	☐		α , n, Di	☐													
A spring torque and the associated swing angle	α		☒																											
A spring torque and the associated swing angle and $\alpha 0$	n, d		☐																											
	n, Di	☐																												
Two spring resistances and the associated swing angle	α , n, d	☐																												
	α , n, Di	☐																												
10 Wire or rod surface ☒ drawn ☐ rolled ☐ metal-cut																														
11 Surface treatment 																														
Prices <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 30%;">Quantity scale</th> <th style="width: 70%;">Single price [EUR]</th> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: right;">5,5300 €</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: right;">3,9000 €</td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: right;">2,7100 €</td> </tr> </table>			Quantity scale	Single price [EUR]	1	5,5300 €	2	3,9000 €	3	2,7100 €																				
Quantity scale	Single price [EUR]																													
1	5,5300 €																													
2	3,9000 €																													
3	2,7100 €																													

Remarks

Country of origin: DE | Customs tariff number: 73202089

Prices

Quantity scale	Single price [EUR]
1	5,5300 €
2	3,9000 €
3	3,7100 €
7	2,9000 €
17	1,4300 €
37	1,1000 €
75	0,9400 €
125	0,6511 €
175	0,6135 €
250	0,5760 €
350	0,5306 €
450	0,4927 €